



RE-VOLT+

AUTOMOTIVE BATTERIES



SPECIFICATIONS

Segment Type	Container Type		Battery Part No.	External Dimensions in mm			Battery Layout	Battery Terminal
	IS	JIS		L	W	H		
COPPER VROOM	N 25/NS 40	B20	06 RCAV 027L	197	129	227	0	T1 - Thin type
	N 25/NS 40	B20	06 RCAV 027R	197	129	227	1	T1 - Thin type
	N 50	D26	06 RCAV 050L	260	173	225	0	T2 - Thick type
	N 50	D26	06 RCAV 050R	260	173	225	1	T2 - Thick type
SILVER VROOM	NS 40	B20	12 RCAV 032L	197	129	227	0	T1 - Thin type
	NS 40	B20	12 RCAV 032R	197	129	227	1	T1 - Thin type
	NS 60(S)	B24	12 RCAV 040L(S)	238	129	227	0	T2 - Thick type
	N 50Z	D26	12 RCAV 060L	260	173	225	0	T2 - Thick type
	N 50Z	D26	12 RCAV 060R	260	173	225	1	T2 - Thick type
	N 70	D31	12 RCAV 070R	306	173	225	1	T2 - Thick type
	N 100	E41	12 RCAV 090L	410	176	234	0	T2 - Thick type
	N 120	F51	12 RCAV 120R	505	182	235	1	T2 - Thick type
	N 150	G51	12 RCAV 150R	508	222	235	1	T2 - Thick type
N 180/N 200	H52	12 RCAV 180R	521	278	240	1	T2 - Thick type	
GOLD VROOM	NS 40Z	B20	18 RCAV 035L	197	129	227	0	T1 - Thin type
	NS 40Z	B20	18 RCAV 035R	197	129	227	1	T1 - Thin type
	NS 60(S)	B24	18 RCAV 045L(S)	238	129	227	0	T2 - Thick type
	N 50Z	D26	18 RCAV 065L	260	173	225	0	T2 - Thick type
	N 50Z	D26	18 RCAV 065R	260	173	225	1	T2 - Thick type
	N 70Z	D31	18 RCAV 075R	306	173	225	1	T2 - Thick type
	N 100	E41	18 RCAV 100L	410	176	234	0	T2 - Thick type
	N 120/N 135	F51	18 RCAV 135R	505	182	235	1	T2 - Thick type
	N 150/N 165	G51	18 RCAV 165R	508	222	235	1	T2 - Thick type
N 200	H52	18 RCAV 200R	521	278	240	1	T2 - Thick type	
PLATINUM DYNALUXE	DIN 044	L1	24 RDIN 044L	206	172	190	0	T2 - Thick type
	DIN 055	L2	24 RDIN 055L	241	172	190	0	T2 - Thick type
	DIN 055	L3	24 RDIN 055R	241	172	190	1	T2 - Thick type
	DIN 066	L3	24 RDIN 066L	277	172	190	0	T2 - Thick type

FEATURES & ADVANTAGES

- Superior starting, powerful lighting with Instant ignition.
- Higher cranking amperes.
- Special paste formulation of battery plates for long life.
- High purity of lead alloy for grids & superfine lead oxide as an active material.
- Low self-discharge.
- Extreme vibration resistance especially designed for rough roads.
- Factory charged & Ready to use batteries.

APPLICATIONS

- Three Wheeler
- Car / Jeep
- SUV / MUV
- Tractor / Construction Equipment
- Light Commercial Vehicles
- Heavy Commercial Vehicles
- Truck / Bus



sales@power-protectors.com
info@power-protectors.com

Our Office Addresses

Power Protectors Canada Limited.
5-2244, Drew Road, Mississauga, Ontario, Toronto, Canada - L5S 1B1, Phone: +1 (437) 777-8797

Power Protectors - USA - 38532
Goodrich Way, Freemont, CA - 94536, USA.
Phone: +1 (905) 965-4288

Power Protectors- Europe
- 12 Cecil Road, London, United Kingdom - E13 0LX,
Phone: +44 7957 658364.

Power Protectors-Australia
- 11 Carbine Street, Box Hill, NSW 2765, Australia,
Phone:- +61 416 607 676.

Power Protectors - MENA
Meydan Free Zone, Meydan Hotel.
P. O. Box No. - 9305, Dubai - UAE.

Power Protectors - India
2/59/1 Sree Colony, Jadavpur, Post Regent Estate, Kolkata: 700092
Phone: 9830419984